

If you need any assistance in helping you understand how to set up your rain fly, feel free to call me at: 770-403-8346

*Your rain fly is shipped with the seams NOT sealed. Since there are no seams directly over the hammock, this should not be an issue. But, it is a good idea to seal all the seams with a good seam sealer before using the hammock in wet weather.*

Your new fly can be set up independently from your camp hammock and used as a ground shelter. When setting up your fly with your hammock, you can set up the fly first (recommended in rainy weather), or set up the hammock first then the fly.

1. **If you have set up the hammock first:** Stand at the hammocks doorway and insure that the peak of the fly is facing you and the fly's stuff sack is to your right. This will place the peak of the fly at the hammocks doorway. Then, holding the fly at the front, throw it over the hammocks ridgeline allowing the fly to lie over the hammock.
2. **Start at the foot of the hammock and pull the hammocks end loop off the toggle button.** Then, from the underside of the fly, insert the hammocks end loop into the rain sleeve at the end wall of the fly and pull it through. Place the hammocks end loop back over the toggle button. Next, connect the fly end loop over the toggle. Repeat this step at the head of the hammock.
3. **Once the fly is connected to the support lines, place the bottom point of your hiking pole into the grommet at the front peak of the fly and the handle of the pole on the ground.** The peak of the fly can be extended to 6 feet.

4. **Stake out the fly starting with the front center guy line first.** Then stake out the center guy line at the back of the rainfly. Next, stake out each end corner at the back of the fly, then each corner at the front of the fly. Ensure the fly is taut.
5. **On the standard fly:** if conditions are stormy, keep the fly peak low and stake the front end corners out wider and more parallel with the hammocks ridgeline. **Your hammock comes with the front tie out line tied to the lowest web loop and will need to be tied to the highest web loop to stake the fly out in a lower position.** This fly can also be allowed to just "hang" over the hammock with out being staked out, once the fly is connected to the support lines. This method can be a benefit in extremely cold but calm wind conditions and allows the hammock to trap more body heat while keeping you dry.
6. **On the full coverage and Snowblind fly:** the peak is designed to be set at its highest position. Once all six guy line tie outs have been staked out, begin to stake out the bottom stake loops of each wall and the front of fly. The fly entry way can be staked open, on both sides or just one, by placing a stake at the doors middle loop, folding the door back and tying it off with the tie line at the top of the door. In stormy conditions, it's best to keep the door closed using the Velcro and staking the door at the two bottom door loops.
7. **To set up the rain fly before setting up the hammock:** Place your two support lines as instructed in the "Hammock Set Up Instructions".
8. **Keep the Long Line at its longest length** and begin attaching the fly to the **Short Line** first by placing the fly's end loop over the toggle button.

9. **Next, attach the end loop of the fly at the foot section (this is the end with the fly's stuff sack) to the Long Line** by placing the loop over the **Long Line** toggle button.
10. **Once both end loops are attached to the support lines,** pull the "tail" of the **Long Line** at the toggle button and tighten the line by holding the toggle with one hand and pushing it toward the tree while pulling on the "tail". Once the fly is taut, begin staking it out as outlined in 3 through 6.
11. **Once the fly is set up you can attach the hammock.** Keep the hammock in its stuff sack and slide the stuff sack end loop through the rain sleeve of the fly at the **Short Line**. Pull the rain fly end loop off the toggle, place the hammock end loop over the toggle, then re-attach the fly end loop back over the toggle. Pull the hammock out of the stuff sack while holding the foot end loop and walking it to the **Long Line**. Pull the rain fly end loop off the **Long Line** toggle and slide the hammock end loop through the rain sleeve on the fly. Attach the hammock end loop over the toggle and re-attach the rain fly end loop over the toggle as well.

**Do not store your fly wet! If you have camped in rainy weather, pull the fly out of the attached stuff sack and hang the fly in a warm dry area and allow the fly to dry completely before storing it back in it's stuff sack.**

**Do not leave your fly out in direct sunlight for an extended period of time. The UVA rays will degrade the ripstop fabric over time.**

**Do not hang your rain fly or hammock near an open flame or fire pit. Be sure to set up your hammock and fly far enough away from a fire pit to insure burning embers do not land on the hammock or fly. Your hammock and fly will not burn but IT WILL MELT.**